

**rationel**<sup>®</sup>

www.rationel.dk/DOP  
www.rationel.co.uk/DOP  
www.rationel.ie/DOP

**Declaration of Performance / Ydeevnedeklaration      Rationel AURA, double glazed / to-lags**

Date / Dato      Herning, 2013/07/01

Revision      DOP-EC-2013/07/01

The performance of the facade windows and the facade doors in the product serie Rationel AURA, double glazed / to-lags are in conformity with the declared in following pages.

This declaration of performance is issued under the sole responsibility of Rationel Vinduer A/S.

Ydeevnen for facadevinduerne og facadedørene i produktserien Rationel AURA, double glazed / to-lags er i overensstemmelse med de deklarerede ydeevner i tabellerne på de følgende sider.  
Denne ydeevnedeklaration udstedes på eneansvar af Rationel Vinduer A/S.

Signed on behalf of Rationel Vinduer A/S:

Underskrevet på vegne af Rationel Vinduer A/S:

**Kurt Bering Sørensen**  
CEO, Administrerende Direktør

**Harmonised technical specication****EN 14351-1:2006 +A1:2010****Harmoniseret teknisk specifikation**

Type of construction product      facade windows and the facade doors  
Byggevareretype      facadevinduerne og facadedøre

Construction product identification      **Rationel AURA, double glazed / to-lags**  
Byggevareidentifikation

Intended use      For domestic and commercial buildings  
Byggevarens tilsigtede anvendelse      Til boliger og erhvervsbygninger

Manufacturer      **Rationel Vinduer A/S**  
Producent

Manufacturer, adress      Dalgas Allé 7, 7400 Herning, DK - Denmark  
Producent, adresse

Name and address of authorised representative      N/A  
Navn og adresse på bemyndiget repræsentant

System of assessment and verification of constancy  
of performance of the construction product      (AVCP) System 3

Systemerne for vurdering af kontrol af konstansen af  
byggevarens ydeevne

**Notified Bodies / Notificerede organer**

**Chiltern Dynamics,**  
Chiltern House, Stocking Lane, Hughenden Valley,  
High Wycombe, HP14 4ND, United Kingdom      **NB 1314**

**Teknologisk Institut,**  
Teknologiparken, Kongsvang Allé 29, 8000 Århus C, Danmark      **NB 1235**

Declaration of Performance / Ydeevnedeklaration Rationel AURA, double glazed / to-lags							DOP-EC-2013/07/01
Element type	Fixed window	Topguided	Sidehung	Sideguided	Sideswing	Fully reversible	Window door
Opening direction	-	Outward	Outward	Outward	Outward	Outward	Outward
Element type	Fast vindue	Topstyret	Sidehængt	Sidestyret	Sidevende	Vendevindue	Vinduesdør
Åbningsretning	-	Udadgående	Udadgående	Udadgående	Udadgående	Udadgående	Udadgående
4.2 Resistance to wind load / Modstandsevne overfor vindlast	1600Pa (4C)	1600Pa (4B)	1600Pa (4B)	1600Pa (4C)	1600Pa (4C)	1600Pa (4C)	1600Pa (4C)
Test and Classification / Test og klassifikation	EN 12211:2000 EN 12210:2000	EN 12211:2000 EN 12210:2000	EN 12211:2000 EN 12210:2000	EN 12211:2000 EN 12210:2000	EN 12211:2000 EN 12210:2000	EN 12211:2000 EN 12210:2000	EN 12211:2000 EN 12210:2000
Notified body / notificeret organ	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314
Test report, issue date / Test rapport, udgivelsesdato	Chilt/p12056/11 February 2013	Chilt/P12056/09/A 2013- 02-13	Chilt/P12056/10 February 2013	Chilt/p12056/13 February 2013	Chilt/p12056/13 February 2013	Chilt/P12056/22 2013- 02-13	Chilt/P12056/17 February 2013
4.5 Watertightness /Vandtæthed	600Pa (9A)	600Pa (9A)	600Pa (9A)	600Pa (9A)	600Pa (9A)	600Pa (9A)	600Pa (9A)
Test and Classification / Test og klassifikation	EN 1027:2000 EN 12208:2000	EN 1027:2000 EN 12208:2000	EN 1027:2000 EN 12208:2000	EN 1027:2000 EN 12208:2000	EN 1027:2000 EN 12208:2000	EN 1027:2000 EN 12208:2000	EN 1027:2000 EN 12208:2000
Notified body / notificeret organ	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314
Test report, issue date / Test rapport, udgivelsesdato	Chilt/p12056/11 February 2013	Chilt/P12056/09/A 2013- 02-13	Chilt/P12056/10 February 2013	Chilt/p12056/13 February 2013	Chilt/p12056/13 February 2013	Chilt/P12056/22 2013- 02-13	Chilt/P12056/17 February 2013
4.8 Load-bearing capacity of safety devices / Sikkerhedsudstyrs bæreevne	N/A	Passed (optional)	Passed (optional)	Passed (optional)	Passed (optional)	Passed	N/A
Test and Classification / Test og klassifikation	-	EN14609:2004	EN14609:2004	EN14609:2004	EN14609:2004	EN14609:2004	
Notified body / notificeret organ	-	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	
Test report, issue date / Test rapport, udgivelsesdato	-	Chilt/P13059, 2013-03-25	Chilt/P13059, 2013-03-25	Chilt/P13059, 2013-03-25	Chilt/P13059, 2013-03-25	Chilt/P12056/12 2013- 02-13 Chilt/P13059, 2013-03-13	
4.11 Acoustic performance / Akustisk ydeevne	NPD	See table below, Se tabel nedenfor Rw (C;Ctr)					NPD
Test and Classification / Test og klassifikation		EN ISO 10140-2:2010	EN ISO 10140-2:2010	EN ISO 10140-2:2010	EN ISO 10140-2:2010	EN ISO 10140-2:2010	
Notified body / notificeret organ		NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	
Test report, issue date / Test rapport, udgivelsesdato		Chilt/Z12014/Ac/Ar1	Chilt/Z12014/Ac/Ar1	Chilt/Z12014/Ac/Ar1	Chilt/Z12014/Ac/Ar1	Chilt/Z12014/Ac/Ar1	
4-24-4 Clear/Energi WE w. argon, 321100000		35 (-1;-4) dB	35 (-1;-4) dB	35 (-1;-4) dB	35 (-1;-4) dB	35 (-1;-4) dB	
4-22-6,4 TGH Clear/Laminated Energy WE w. argon, 321120003		39 (-1;-5) dB	39 (-1;-5) dB	39 (-1;-5) dB	39 (-1;-5) dB	39 (-1;-5) dB	
4-22-6,8 TGH Clear/Laminated Energy WE w. argon, 321120004		39 (-1;-5) dB	39 (-1;-5) dB	39 (-1;-5) dB	39 (-1;-5) dB	39 (-1;-5) dB	
6-18-8.8 Clear/Sound Laminated Energy WE w. argon, 321100110		40 (-1;-4) dB	40 (-1;-4) dB	40 (-1;-4) dB	40 (-1;-4) dB	40 (-1;-4) dB	
4-20-8.8 Clear/Sound Laminated Energy WE w. argon, 321100010		40 (-1;-5) dB	40 (-1;-5) dB	40 (-1;-5) dB	40 (-1;-5) dB	40 (-1;-5) dB	
4-22-6 Clear/Energi WE w. argon, 321100001		37 (1;-6) dB	37 (1;-6) dB	37 (1;-6) dB	37 (1;-6) dB	37 (1;-6) dB	
6,8-16-8,8 Laminated Clear / Sound Laminated Energi WE w. argon, 321110310		41 (-1;-4) dB	41 (-1;-4) dB	41 (-1;-4) dB	41 (-1;-4) dB	41 (-1;-4) dB	
4-18-9,5 Clear/Laminated Energy WE w. argon, 321100007		37 (0;-3) dB	37 (0;-3) dB	37 (0;-3) dB	37 (0;-3) dB	37 (0;-3) dB	
Note	Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 + A1:2010, Table E.2, Note d.						
Note	Thermal transmissionskoefficient (4.12) og strålingsegenskaber (4.13) for et specifikt produkt er angivet på tilbud/ordrebekræftelse i overensstemmelse med EN 14351-1:2006 + A1:2010, Tabel E.2, Note d.						
4.12 Thermal transmittance / Termisk transmissionskoefficient	1,28 (W/m2K)	1,28 (W/m2K)	1,28 (W/m2K)	1,28 (W/m2K)	1,28 (W/m2K)	1,28 (W/m2K)	1,28 (W/m2K)
Test and Classification / Test og klassifikation	EN ISO 10077-2:2011	EN ISO 10077-2:2011	EN ISO 10077-2:2011	EN ISO 10077-2:2011	EN ISO 10077-2:2011	EN ISO 10077-2:2011	EN ISO 10077-2:2011
Notified body / notificeret organ	NB 1235	NB 1235	NB 1235	NB 1235	NB 1235	NB 1235	NB 1235
Test report, issue date / Test rapport, udgivelsesdato	516699 Rationel AURA (2) ITC 2013-05-14	516699 Rationel AURA (2) ITC , 2013-05-14	516699 Rationel AURA (2) ITC , 2013-05-14	516699 Rationel AURA (2) ITC , 2013-05-14	516699 Rationel AURA (2) ITC , 2013-05-14	516699 Rationel AURA (2) ITC , 2013-05-14	516699 Rationel AURA (2) ITC , 2013-05-14
4.13 Radiation properties / Strålingsegenskaber	g 0,63 LT 0,80	g 0,63 LT 0,80	g 0,63 LT 0,80	g 0,63 LT 0,80	g 0,63 LT 0,80	g 0,63 LT 0,80	g 0,63 LT 0,80
4.14 Air permeability / Lufttæthed	600Pa (4)	600Pa (4)	600Pa (4)	600Pa (4)	600Pa (4)	600Pa (4)	600Pa (4)
Test and Classification / Test og klassifikation	EN1026:2000 EN12207:2000	EN1026:2000 EN12207:2000	EN1026:2000 EN12207:2000	EN1026:2000 EN12207:2000	EN1026:2000 EN12207:2000	EN1026:2000 EN12207:2000	EN1026:2000 EN12207:2000
Notified body / notificeret organ	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314
Test report, issue date / Test rapport, udgivelsesdato	Chilt/p12056/11 February 2013	Chilt/P12056/09/A 2013- 02-13	Chilt/P12056/10 February 2013	Chilt/p12056/13 February 2013	Chilt/p12056/13 February 2013	Chilt/P12056/22 2013- 02-13	Chilt/P12056/17 February 2013
4.16 Operating forces / Betjeningskraft	N/A	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1
Test and Classification / Test og klassifikation		EN12046-1:2003 EN13115:2001	EN12046-1:2003 EN13115:2001	EN12046-1:2003 EN13115:2001	EN12046-1:2003 EN13115:2001	EN12046-1:2003 EN13115:2001	EN12046-1:2003 EN13115:2001
Notified body / notificeret organ		NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314
Test report, issue date / Test rapport, udgivelsesdato		Chilt/P12056/09/A 2013- 02-13	Chilt/P12056/10 February 2013	Chilt/p12056/13 February 2013	Chilt/p12056/13 February 2013	Chilt/P12056/12 2013-02-13	Chilt/P12056/15 February 2014
4.17 Mechanical strength / Mekanisk styrke	Class 3	Class 3	Class 3	Class 3	Class 3	Class 3	Class 3
Test and Classification / Test og klassifikation		EN14608:2004 EN14609:2004 EN13115:2001	EN14608:2004 EN14609:2004 EN13115:2001	EN14608:2004 EN14609:2004 EN13115:2001	EN14608:2004 EN14609:2004 EN13115:2001	EN14608:2004 EN14609:2004 EN13115:2001	EN14608:2004 EN14609:2004 EN13115:2001
Notified body / notificeret organ		NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314
Test report, issue date / Test rapport, udgivelsesdato		Chilt/P12056/09/A 2013- 02-13	Chilt/P12056/10 February 2013	Chilt/p12056/13 February 2013	Chilt/p12056/13 February 2013	Chilt/P12056/12 2013-02-13	Chilt/P12056/15 February 2014
4.21 Resistance to repeated opening and closing / Modstandsevne for gentagen åbning og lukning	N/A	20.000 Class 3	20.000 Class 3	20.000 Class 3	20.000 Class 3	20.000 Class 3	20.000 Class 3
Test and Classification / Test og klassifikation		EN 1191:2000 EN 12400:2002	EN 1191:2000 EN 12400:2002	EN 1191:2000 EN 12400:2002	EN 1191:2000 EN 12400:2002	EN 1191:2000 EN 12400:2002	EN 1191:2000 EN 12400:2002
Notified body / notificeret organ		NB 1314	NB 1314	NB 1314	NB 1314	NB 1314	NB 1314
Test report, issue date / Test rapport, udgivelsesdato		Chilt/P12056/09/A 2013- 02-13	Chilt/P12056/10 February 2013	Chilt/p12056/13 February 2013	Chilt/p12056/13 February 2013	Chilt/P12056/12 2013-02-13	Chilt/P12056/15 February 2014

Declaration of Performance / Ydeevnedeclaration Rational AURA, double glazed / to-lags						DOP-EC-2013/07/01
Element type	Terrace door	Terrace door	Entrance door	Entrance door	Panelled door	Panelled door
Opening direction	Inward opening	Outward	Inward opening	Outward	Inward opening	Outward
Element type	Terrassedør	Terrassedør	Rammedør	Rammedør	Pladedør	Pladedør
Åbningsretning	Indadgående	Udadgående	Indadgående	Udadgående	Indadgående	Udadgående
4.2 Resistance to wind load / Modstandsevne overfor vindlast	NPD	NPD	NPD	NPD	NPD	NPD
Test and Classification / Test og klassifikation						
Notified body / notificeret organ						
Test report, issue date / Test rapport, udgivelsesdato						
4.5 Watertightness / Vandtæthed	NPD	NPD	NPD	NPD	NPD	NPD
Test and Classification / Test og klassifikation						
Notified body / notificeret organ						
Test report, issue date / Test rapport, udgivelsesdato						
4.8 Load-bearing capacity of safety devices / Sikkerhedsudstyrs bæreevne	N/A	N/A	N/A	N/A	N/A	N/A
Test and Classification / Test og klassifikation	-	-	-	-	-	-
Notified body / notificeret organ	-	-	-	-	-	-
Test report, issue date / Test rapport, udgivelsesdato	-	-	-	-	-	-
4.11 Acoustic performance / Akustisk ydeevne	NPD	NPD	NPD	NPD	NPD	NPD
Test and Classification / Test og klassifikation						
Notified body / notificeret organ						
Test report, issue date / Test rapport, udgivelsesdato						
Note	Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 + A1:2010, Table E.2, Note d.					
Note	Thermal transmissionskoefficient (4.12) og strålingsegenskaber (4.13) for et specifikt produkt er angivet på tilbud/ordrebekræftelse i overensstemmelse med EN 14351-1:2006 + A1:2010, Tabel E.2, Note d.					
4.12 Thermal transmittance / Termisk transmissionskoefficient	1,28 (W/m2K)	1,26 (W/m2K)	1,28 (W/m2K)	1,26 (W/m2K)	0,61 (W/m2K)	0,59 (W/m2K)
Test and Classification / Test og klassifikation	EN ISO 10077-2:2003	EN ISO 10077-2:2003	EN ISO 10077-2:2003	EN ISO 10077-2:2003	EN ISO 10077-2:2003	EN ISO 10077-2:2003
Notified body / notificeret organ	NB 1235	NB 1235	NB 1235	NB 1235	NB 1235	NB 1235
Test report, issue date / Test rapport, udgivelsesdato	478300 Rational - beregningsrap ITT Aura 2-lags, 2012-05-30	478300 Rational - beregningsrap ITT Aura 2-lags, 2012-05-30	478300 Rational - beregningsrap ITT Aura 2-lags, 2012-05-30	478300 Rational - beregningsrap ITT Aura 2-lags, 2012-05-30	478300 Rational - beregningsrap ITT Aura 2-lags, 2012-05-30	478300 Rational - beregningsrap ITT Aura 2-lags, 2012-05-30
4.13 Radiation properties / Strålingsegenskaber	g 0,63 LT 0,80	g 0,63 LT 0,80	g 0,63 LT 0,80	g 0,63 LT 0,80	-	-
4.14 Air permeability / Lufttæthed	NPD	NPD	NPD	NPD	NPD	NPD
Test and Classification / Test og klassifikation						
Notified body / notificeret organ						
Test report, issue date / Test rapport, udgivelsesdato						
4.16 Operating forces / Betjeningskraft	NPD	NPD	NPD	NPD	NPD	NPD
Test and Classification / Test og klassifikation						
Notified body / notificeret organ						
Test report, issue date / Test rapport, udgivelsesdato						
4.17 Mechanical strength / Mekanisk styrke	NPD	NPD	NPD	NPD	NPD	NPD
Test and Classification / Test og klassifikation						
Notified body / notificeret organ						
Test report, issue date / Test rapport, udgivelsesdato						
4.21 Resistance to repeated opening and closing / Modstandsevne for gentagen åbning og lukning	NPD	NPD	NPD	NPD	NPD	NPD
Test and Classification / Test og klassifikation						
Notified body / notificeret organ						
Test report, issue date / Test rapport, udgivelsesdato						