

<p align="center">SCOPE OF CERTIFICATION Enhanced Security Doorset to PAS24:2016</p> <p align="center">Manufacturer of Enhanced Security Doorsets in accordance with BM TRADA Q-Mark Scheme requirements. (Check with Secured by Design to ensure compliance with any additional requirements)</p>			
Head Office Dovista A/S Bygholm Søpark 21D 8700 Horsens Denmark	Manufacturing Site Dovista Polska SP z.o.o Wędkowy 83-115 Swarozyn Poland	 Proud to be part of  This scope of certification supports Certificate Number 050/110 The validity of this scope document should be checked against the current schedule of the Company's certification listed on the BM TRADA website www.bmtrada.com .	
Completed: P. Andrews 	Checked: P. Wren 		
Scope number: D110-004			
Issue: 5	Date: 25 April 2022	Details: Review of scope	
Product Name: <p align="center">FORMA Entrance Doorset Range</p> <p align="center">Outward Opening, Single and double leaf, Timber Doorset With or Without Sidelight or Toplight</p> <p align="center">FORMAPLUS Entrance Doorset Range</p> <p align="center">Outward Opening, Single and double leaf, Timber Doorset with aluminium cladding With or Without Sidelight or Toplight</p> <p align="center">AURA Entrance Doorset Range</p> <p align="center">Outward Opening, Single and double leaf, Timber Doorset With or Without Sidelight or Toplight</p> <p align="center">AURAPLUS Entrance Doorset Range</p> <p align="center">Outward Opening, Single and double leaf, Timber Doorset with aluminium cladding With or Without Sidelight or Toplight</p>		This document remains the intellectual property of BM TRADA. It shall not be made available to another person or company without the prior written permission of BM TRADA.	
Doorset classification 'D'		Test evidence is held on file by BM TRADA	
All Q-Mark certified doorsets must have evidence to demonstrate that the profiles, components and manufacturing procedures used meet the requirements of the appropriate material specific standards: BS 644 (timber); BS 4873 (aluminium); BS 6510 (steel); BS 7412 (PVC-U); BS 8529 (composite).			

Weather rating

BS6375 part 1 Exposure category **1200** (on largest specimen)

Maximum door leaf size

Open out (not including frame)

1138mm wide x 2460mm high excluding false mullion
 1166mm wide x 2460mm high including false mullion